

Sublimation from A to Z:

EQUIPMENT: plotters, roll and flat heat pressers (manufacturer)

MEDIA: sublimation inks, sublimation papers, protective (brown) papers

SERVICES: printing of sublimation papers on plotter

PP 002 Heat press

for double side tape transferring at the same time



TECHNICAL DATA:

- 2 heating plates: 310 x 560 mm
- speed for 30 s heating: 1.120 mm/min
- speed for 40 s heating: 840 mm/min
- temperature regulation: every 1°C up to 220°C (every 34°F up to 410°F)
- transferring time regulation
- pneumatic pressure regulation of plates
- system of the precise adjustment of transferred images on both sides of tape
- max. power consumption: 6,5 kW
- min. power consumption: 60 W
- power: 3 x 400 V, 1 x 230 V
- weight: 400 kg
- dimensions: L=1.360 mm, H=1.560 mm, w=720 mm
- compressed air: appx. 1,5 l/cycle, 6 bar
- special equipment allowing transferring on lanyards: 5, 10, 15, 20, 25 mm (0,2", 0,39", 0,59", 0,79", 0,98") etc.
or we can adjust table to your particular needs or used tapes width.

SECURITY:

- 2 x E stop
- the automatic disconnection of the machine in case of errors of the steering drive or the lack of the compressed air

OTHER:

- CE declaration
- DTR
- Made in Poland
- Customs tariff: 84 5180 30

EFFICIENCY:

- 750 pcs/1 h, double side printed lanyards, 15 mm width (0,59")/1h

PP002_ENG